

SPECIFICATIONS

BP20 Barometric Pressure Sensor

FEATURES

- High level linear voltage output
- Full-span or half-span output option



The NRG #BP20 barometric pressure sensor is a micro-machined absolute pressure sensor which provides a high level voltage output signal that is proportional to absolute pressure. It includes built-in temperature compensation, linearization, and an output amplifier.

Its low cost and rugged PVC enclosure make the BP-20 ideal for collecting absolute pressure data at remote sites.

SPECIFICATIONS

Description	Sensor type	micro-machined integrated circuit absolute pressure sensor
	Applications	<ul style="list-style-type: none"> • wind resource assessment • meteorological studies • environmental monitoring
	Sensor range	15 kPa to 115 kPa (4.43 inches to 34.0 inches Hg)
	Instrument compatibility	<ul style="list-style-type: none"> • NRG Symphonie equipped with a BP SCM + any iPack • any NRG 9300SA, NRG 9300CL or 9300TL equipped with a TPRH SIM card + PV/battery
Output signal	Signal type	linear analog voltage
	Transfer function	Absolute Pressure in kPa = (Voltage x 21.79) + 10.55 typical
	Accuracy	+/- 1.5 kPa max. uncorrected offset (+/- 0.443 inches Hg)
	Calibration	calibration sheet included with each sensor specifies offset correction
	Turn on time	15 ms
Power requirements	Supply voltage	7 V to 35 V DC
	Supply current	15 mA max. (8 mA typical)
Installation	Mounting	mounts directly to tower or inside steel shelter box with hose clamps (included)
	Tools required	5/16 inch hex driver or flat blade screwdriver



Global leaders in wind assessment technology

110 Riggs Road • Hinesburg • VT 05461 USA • TEL (802) 482-2255 • FAX (802) 482-2272 • EMAIL sales@nrgsystems.com

SPECIFICATIONS

Physical	Connections	wire leads: <ul style="list-style-type: none">• signal (green wire)• ground (black wire)• excitation (red wire)• half-span signal (white wire)• shield wire for earth ground
	Cable length	<ul style="list-style-type: none">• 1.5 m (5 feet)• cable diameter 4.8 mm (3/16 inches)
	Weight	0.1 kg (0.2 pounds)
	Dimensions	<ul style="list-style-type: none">• 57 mm (2.25 inches) diameter• 112 mm (4.4 inches) length (including cable bushing)
Materials	Cable	4 conductor 22 AWG, with overall foil shield and drain wire, chrome PVC jacket
	Enclosure	weatherproof PVC



Global leaders in wind assessment technology

110 Riggs Road • Hinesburg • VT 05461 USA • TEL (802) 482-2255 • FAX (802) 482-2272 • EMAIL sales@nrgsystems.com