

# SPECIFICATIONS

## NRG #40 Anemometer

### FEATURES

- The standard anemometer used in the wind energy industry
- Short distance constant
- Simple, durable design



The NRG #40 anemometer is the industry standard anemometer used worldwide. NRG #40 anemometers have recorded wind speeds of 96 m/s (214 mph). Their low moment of inertia and unique bearings permit very rapid response to gusts and lulls. Because of their output linearity, these sensors are ideal for use with various data retrieval systems. A four pole magnet induces a sine wave voltage into a coil producing an output signal with a frequency proportional to wind speed. The #40 is constructed of rugged Lexan cups molded in one piece for repeatable performance. A rubber terminal boot is included.

### SPECIFICATIONS

Description	Sensor type	3-cup anemometer
	Applications	<ul style="list-style-type: none"><li>• wind resource assessment</li><li>• meteorological studies</li><li>• environmental monitoring</li></ul>
	Sensor range	1 m/s to 96 m/s (2.2 mph to 214 mph) (highest recorded)
	Instrument compatibility	all NRG loggers
Output signal	Signal type	low level AC sine wave, frequency linearly proportional to windspeed
	Transfer function	$m/s = (Hz \times 0.765) + 0.35$ [miles per hour = $(Hz \times 1.711) + 0.78$ ]
	Accuracy	within 0.1 m/s (0.2 mph) for the range 5 m/s to 25 m/s (11 mph to 55 mph)
	Calibration	calibrated version available
	Output signal range	0 Hz to 125 Hz (highest recorded)
Response characteristics	Threshold	0.78 m/s (1.75 miles per hour)

Global leaders in wind assessment technology



110 Riggs Road • Hinesburg • VT 05461 USA • TEL (802) 482-2255 • FAX (802) 482-2272 • EMAIL sales@nrssystem.com

# SPECIFICATIONS

	Distance constant (63% recovery)	3.0 m (10 feet)
	Moment of inertia	$68 \times 10^{-6} \text{ S-ft}^2$
	Swept diameter of rotor	190 mm (7.5 inches)
Installation	Mounting	onto a 13 mm (0.5 inch) diameter mast with cotter pin and set screw
	Tools required	0.25 inch nut driver, petroleum jelly, electrical tape
Environmental	Operating temperature range	-55 °C to 60 °C (-67 °F to 140 °F)
	Operating humidity range	0 to 100% RH
Physical	Connections	4-40 brass hex nut/post terminals
	Weight	0.14 kg (0.3 pounds)
	Dimensions	<ul style="list-style-type: none"> <li>• 3 cups of conical cross-section, 51 mm (2 inches) dia.</li> <li>• 81 mm (3.2 inches) overall assembly height</li> </ul>
Materials	Cups	one piece injection-molded black polycarbonate
	Body	housing is black ABS plastic
	Shaft	beryllium copper, fully hardened
	Bearing	modified Teflon, self-lubricating
	Magnet	Indox 1, 25 mm (1 inch) diameter, 13 mm (0.5 inch) long, 4 poles
	Coil	single coil, bobbin wound, 4100 turns of #41 wire, shielded for ESD protection
	Boot	protective PVC sensor terminal boot included
	Terminals	brass

*Global leaders in wind assessment technology*



110 Riggs Road • Hinesburg • VT 05461 USA • TEL (802) 482-2255 • FAX (802) 482-2272 • EMAIL [sales@nrgsystems.com](mailto:sales@nrgsystems.com)