

Product Features



Positive tolerance

Guaranteed tolerance +3%
Reliable power output



High module efficiency

Module efficiency up to 15.7%
Cells efficiency up to 17.8%



Strong compressive strength

Certified to withstand high wind of 2400Pa
and snow loads of 5400Pa



High manufacture standards

certified to high standards by the
most reputable labs According to
IEC:61215: IEC:61730-1/2



International Management System

Manufactured and certified according
to ISO9001, Quality management system



Fire test approved

Application class A, Safety Class II, Fire Rating C



Excellent performance under extreme condition

High salt mist and ammonia resistance




Reliable quality forever

Without potential induced
degradation (PID-free)

Leading Warranty in PV Industry

- 25 year transferrable power output warranty: 10 years / 90%, 25 years / 80%
- Linear performance warranty from SIMAX Power
- 12 year material and workmanship warranty



* Please refer to Simax Solar Product Warranty for details.



Electrical Characteristics

Parameters	SP672-280		SP672-285		SP672-290		SP672-295		SP672-300		SP672-305		SP672-310	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Peak power [Wp] P_{mpp}	280W	208W	285W	212W	290W	215W	295W	219W	300W	226W	305W	224W	310W	228W
Open circuit voltage [V] V_{oc}	44.4	44.7	44.4	45.0	44.4	45.3	45.0	45.5	45.0	45.8	45.2	45.8	45.5	45.8
Maximum Power Voltage [V] (V_{mpp})	29.5	37.2	35.8	37.4	35.8	37.4	36.3	37.8	36.3	38.0	36.5	38.0	36.8	38.0
Maximum Power Current [A] (I_{mpp})	7.82	5.59	7.96	5.65	8.10	5.76	8.13	5.79	8.26	5.95	8.35	5.91	8.42	6.05
Short circuit Current [A] (I_{sc})	8.45	5.94	8.60	5.99	8.71	6.06	8.78	6.12	8.93	6.25	8.95	6.89	9.01	7.21
Power Tolerance	0~+3%		0~+3%		0~+3%		0~+3%		0~+3%		0~+3%		0~+3%	
Module Efficiency (%)	14.5%		14.7%		14.9%		15.3%		15.5%		15.7%		16.0%	

STC: Irradiance : 1000 W/m² ; Spectrum AM 1.5; Cell temperature: 25°C; Wind 0 m/s
 NOCT: Irradiance: 800W/m² ; Spectrum AM 1.5; ambient temperature 20°C, wind speed 1 m/s

Mechanical Characteristics


Solar Cell	Polycrystalline silicon 156 x 156 (mm)
No. of Cells	72 (6 x 12)
Dimensions	1956 x 992 x 40 mm
Weight	22.5 kg
Front Glass	3.2mm (0.13 inches) tempered glass
Frame	Anodized aluminum alloy

Output



Cable Type	Ø = 4 mm ²
Lengths	L = 900 mm
Junction Box	PV - JB001 MC4

Temperature Coefficients

Nominal Operating Cell Temperature (NOCT)	45 ± 2°C
Temperature Coefficient of (P_{max})	-0.39% / °C
Temperature Coefficient of (V_{oc})	-0.34% / °C
Temperature Coefficient of (I_{sc})	0.035% / °C



- Provide the best solutions for photovoltaic power generation and technical support
- Provide Cost-effective products
- Provide 12 Years Quality Warranty
- Power out ≥ 90% in 10 years
- Power out ≥ 80% in 25 years



Global standby to ensure response within 24 hours
 Australia and Europe office were established to give better services to customers

Simax Green New Energy (Europe) GmbH
 Mergenthaler Allee 23 / 25
 65760 Eschborn / Germany
 Tel.: +49 6196 9739 525
 Fax: +49 6196 5929 684
 info@simaxsolar.de
 www.simaxsolar.de



Simax (Australia) Green New Energy Pty Ltd
 5 / 78 Frankston Gardens Drive,
 Carrum Downs, VIC 3210
 Tel: +61 3 9708 2400
 Fax: +61 3 9708 2482
 info@simaxsolar.com.au
 www.simaxsolar.com.au

